# Anticlockwise 5.4hp Air Cooled Diesel Engine 3000RPM 3600RPM

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Price:
- Delivery Time:

China

GET

ISO CE

- Payment Terms:
- Negotiable 15-20 workdays LC, T/T, PayPal, Western Union, Smallamount payment, Money Gram



# **Product Specification**

• Туре:	Single Cylinder, Vertical, Four-stroke, Direct Injection, Air-cooled
Borexstroke:	73x59mm, 78x62mm, 86x72mm
<ul> <li>Displacement:</li> </ul>	247ml, 296ml, 418ml
Compression Ratio:	20:01, 20:01, 19:01
• Rated Power(kw/rpm):	3.5/3000-3.8/3600 3.68/3000- 4/3600 5.7/3000-6.3/3600
• Rated Power(hp/rpm):	4.8/3000-5.2/3600, 5.0/3000-5.4/3600, 7.8/3000-8.6/3600
<ul> <li>Rated Speed(rpm):</li> </ul>	3000/3600
Lowest Rotation Speed At Zero Load:	≤1300r/min
<ul> <li>Lubricating System:</li> </ul>	Pressure Splashed
<ul> <li>Starting System:</li> </ul>	Recoil Start/electric Starter
• Rotation Direction(face To The Output Axle ):	Anticlockwise
Fuel Turner	O#(aummar) 10#(wintar) 2E#(ahillaaca)

### GET173F GET178F GET186FA Single Cylinder Air Cooled Diesel Engine

A single-cylinder air-cooled diesel engine is a type of internal combustion engine that has a single cylinder and relies on air cooling to maintain the operating temperature. It is commonly used in small applications, such as generators, water pumps, agricultural equipment, and small vehicles.

Here are some key features and characteristics of a single-cylinder air-cooled diesel engine:

Cylinder: It has a single cylinder in which the combustion process takes place. The piston moves up and down within the cylinder, converting the energy of combustion into mechanical work.

Air Cooling: Instead of using a liquid coolant and radiator system, these engines rely on air cooling to dissipate heat. They typically have cooling fins on the outside surface of the cylinder and sometimes on the cylinder head to increase the surface area for better heat dissipation.

Compression Ignition: Diesel engines operate on the principle of compression ignition, where fuel is injected into the combustion chamber at high pressure. The compressed air in the cylinder heats up and ignites the fuel without the need for a spark plug.

Fuel Injection: Fuel is injected into the combustion chamber using a fuel injection system. Commonly, these engines use direct fuel injection, where fuel is injected directly into the combustion chamber.

Efficiency and Torque: Diesel engines are known for their high efficiency and torque output. They are generally more fuelefficient than gasoline engines and provide higher torque at lower RPMs, making them suitable for applications that require heavy loads to be driven.

Simplicity and Reliability: Single-cylinder air-cooled diesel engines are relatively simple in design, which makes them reliable and easy to maintain. They have fewer moving parts compared to multi-cylinder engines, reducing the chances of component failure.

Noise and Vibration: Single-cylinder engines tend to produce more noise and vibration compared to multi-cylinder engines. However, advancements in engine design and technology have helped reduce noise and vibration levels significantly. Power Output: The power output of a single-cylinder air-cooled diesel engine can vary depending on its size and design. Typically, they have lower power outputs compared to multi-cylinder engines, but they are still capable of providing sufficient power for their intended applications.

It's important to note that while single-cylinder air-cooled diesel engines have their advantages in terms of simplicity and reliability, they may not be suitable for applications that require higher power output or smoother operation. In such cases, multi-cylinder engines with liquid cooling may be preferred.

Model	GET188F	GET190F	GET192F	GET195F		
Туре	four-stroke, direct injection,	four-stroke, direct injection,				
	air-cooled	air-cooled	air-cooled	air-cooled		
Bore*Stroke	88.75*90mm	75*77mm	92*75mm	95*75mm		
Displacement	19:01cc	19:01cc	19:01cc	19:01cc		
Compression Ratio	6.7/3000	7.8/3000	6.5/3000	8.1/3000		
Rated Power (KWipm)	7.2/3600	7.3/3600	8.2/3600	8.7/3600		
Rated Power (HPIIPm)	9.8/3600	10.3/3600	112/3600	11.8/3600		
Rated Speed (rpm)		3000/3600				
Lowest rotation speed at zero loed		1300				
Lubricating system		Pressure splashad	Pressure splashad	Pressure splashad		



13813650506

P

D 9 March		GETINE	GETTINF	GETTINFA		
HIZ Type		#41. E.E. BE. ER. ROBER Inge optide, which, for -drifts, deal readon, ar-costed				
128-788 Bondinte	- mm	7719	10100	00.12		
H B Depacement	- 16	197	298	48		
Edit Compression Page		20101	0001	1901		
MECR Ruled Foreir	mation	0.5/9000 3.8/9800	1.0000000 4/3000	5.1380 6.3380		
#208 hated Poster	1 Pages	4.8/2000 5.2/2000	1.0000 8.40800	18300 84300		
BERFER Faired Speed	494	3000 / 3600				
#4.0400000000 Lowent science speechal zero hand	-100	< 100				
RRhd ubrang ween		B.X.1.B.Z. Propuls updated				
Billichal Stanling summer		RGR/SER/SER Recul Service de la service de l				
Notation direction does to the subject anks		BITT ANDOWN				
MART Task System		C0 1201-00 1001-00 100102102010210400-104 Conter1-004 (000es) dead				
BARTE Ford lark capacity	. L.	2.8	3.8	8.8		
Mahik@@ili291# Fail consumption/ selectorization speedgraft (vmar)		200.27000 200.37000	676.10000 005.50000	(25.1000) (01.51000)		
NRMMPH Lide-St Spe		00 page-or 546 mm-dt, 15M-dt				
REBUS Lide of Ispecty	L.	6.75	1.1	1.05		
GROUND Starting make squarity	11,107	10/06/8				
nikolikuwa Dianging perakakin sapasily	N. 8	127 8.38				
ROATE failey spacing	N. 88	101 20m	GV 204	12V 30Ah		
PART Overal developer (L = W = H1	ma	42014001488	48014801010	307407343		
## to want	14	28	10			

@ dieselenginepumps.com

## **GET** Wuxi Guangertai Power Machinery Co.,Ltd

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA

2415819289@qq.com