

# 12HP 25 HP Air Cooled Diesel Engine 10HP Air Cooled Diesel Motor

## **Basic Information**

Place of Origin: China
Brand Name: GET
Certification: ISO CE
Price: Negotiable
Delivery Time: 15-20 workdays

Payment Terms:
 LC, T/T, PayPal, Western Union, Small-

amount payment, Money Gram



# **Product Specification**

• Type: Single Cylinder, Vertical, Four-stroke, Direct

Injection, Air-cooled

Borexstroke: 73x59mm, 78x62mm, 86x72mm

Displacement: 247ml, 296ml, 418ml
 Compression Ratio: 20:01, 20:01, 19:01

 Rated Power(kw/rpm): 3.5/3000-3.8/3600 3.68/3000-4/3600 5.7/3000-6.3/3600

• Rated Power(hp/rpm): 4.8/3000-5.2/3600, 5.0/3000-5.4/3600,

7.8/3000-8.6/3600

Rated Speed(rpm): 3000/3600
Lowest Rotation Speed At ≤1300r/min

Zero Load:

Lubricating System: Pressure SplashedStarting System: Recoil Start/electric Starter

• Rotation Direction(face To Anticlockwise

The Output Axle ):

First Times 0#/simmer\ 10#/winter\ 0E#/shillness\

### **Product Description**

#### GET192F 10hp 12hp 25hp Air Cooled Diesel Engine Air Cooled Diesel Generator

An air-cooled diesel generator is a type of generator that utilizes an air-cooling system to dissipate the heat generated during its operation. It consists of a diesel engine coupled with an alternator to produce electrical power. Here are some key features and advantages of air-cooled diesel generators:

Cooling System: Instead of relying on a liquid cooling system with a radiator and coolant, air-cooled generators use a combination of cooling fins and fans to circulate air and cool the engine. This design eliminates the need for a separate cooling system, making the generator more compact and easier to maintain.

Durability and Reliability: Air-cooled diesel generators are known for their robustness and reliability. The absence of a liquid cooling system reduces the risk of coolant leaks and associated maintenance issues. They are often chosen for applications where durability and continuous operation are critical.

Low Maintenance: Air-cooled generators generally require less maintenance compared to liquid-cooled generators. With no coolant to monitor or replace, there are fewer maintenance tasks involved. However, regular maintenance such as oil changes, filter replacements, and general inspection are still necessary to ensure optimal performance.

Portability: Due to their compact design and lighter weight compared to liquid-cooled generators, air-cooled diesel generators are more portable and easier to transport. This makes them suitable for applications where mobility is required, such as construction sites or outdoor events.

Cost-effectiveness: Air-cooled generators generally have a lower upfront cost compared to liquid-cooled generators. They are often more affordable to purchase and maintain, making them a popular choice for smaller-scale applications and budgetconscious users.

Ambient Temperature Considerations: It's important to note that air-cooled generators are affected by ambient temperature. In hot climates or high-temperature conditions, their cooling efficiency may be reduced, potentially impacting their performance. Adequate ventilation and proper placement of the generator are necessary to ensure optimal cooling in such environments.

Model	GET188F	GET190F	GET192F	GET195F
Туре	vertical, four-stroke, direct injection, air- cooled		vertical, four-stroke,	Single cylinder, vertical, four-stroke, direct injection, air- cooled
	88.75*90mm	75*77mm	92*75mm	95*75mm
Displacem ent		19:01cc	19:01cc	19:01cc
Compressi on Ratio	6.7/3000	7.8/3000	6.5/3000	8.1/3000
Rated Power (KWipm)	7.2/3600	7.3/3600	8.2/3600	8.7/3600
Rated Power (HPIIPm)	9.8/3600	10.3/3600	112/3600	11.8/3600
Rated Speed (rpm)		3000/3600		
Lowest rotation speed at zero loed		1300		
Lubricatin g system		Pressure splashad	Pressure splashad	Pressure splashad

When considering an air-cooled diesel generator, it's essential to assess your power requirements, intended applications, and environmental conditions to determine if it aligns with your needs. Additionally, consulting with a reputable generator supplier or manufacturer can provide you with specific information on available models and their capabilities.



REType		#EL, E.E., IEE, E.R. RIMBER Englishman, vehicle for chick, drug readon, or-code:				
USTER Bondone	me	rores	rese	80.12		
HB Displacement	16	(41)	296	48		
Edit Corposión Fallo		2001	0041	1901		
MESS Ruled From	minon	9.5/9000 9.8/9800	3.000000 4.5000	5.7980 6.3360		
BERT had have	Hipm	4,9'0000 5,2'0000	1.0'000 1.4'000	1,0300		
SECTION States Speed	ger	3000 / 3000				
BETTERNING Lound solder special and had	1000	< 100				
Will the company of t		EX18E People-system				
Billiote Starting system		EGRS Fed R Food Service stude				
Michigan (Epithalia) Relation desclaration to the output solid		BETT ATLANTAGE				
MARIE Facilities		C+   \$3.1 - 10.4   6.5.1 - 10.4   6.81   6.82   4.1   number 2 - 10.4   number 1 - 20.4   0.00   encil				
BARRY For live capacity	L.	2.0	3.0	8.6		
MARKERSONE Fairmanyon MERCHEN SHEET FAIRMAN		290-27000E 290-27000E	676.10000 000.870000	\$75,10000 \$81,51000		
REMARK Lide of type		(O gade or Self 1994-91, 1994-91				
RFB9B Lite-Hisparity	L.	175		1.00		
G In Table Starting mater reportly	11,100	10/16/8				
neperate Darping prender repeals	V. 8	129.83A				
ESSE Sales specily	V. m	501 20th	59° 204-	12V 36An		
MERCE Countries on I Law Plant I	ma	43014001488	460*460*010	30740740		
## to want	No.		76	- 4		











NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA