



2500E Open Frame Generator 0.9KW 1.2KW 1 Cylinder Diesel Generator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Output(kw): 1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
- Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- Insulation Grade: F
- Pole Number: 2
- Excitation Mode: Self-excitation & Constant Voltage (AVR)
- Panel Type: General Panel

for more products please visit us on dieselenginepumps.com

Product Description

GET2500E Single Phase Open Type Diesel Generator Open Type Genset

An open type diesel generator refers to a generator set that is designed without an enclosure or housing surrounding the engine and alternator. It is also commonly known as an open frame or open skid generator. Here is a description of an open type diesel generator:

Engine: The open type diesel generator is equipped with a diesel engine as its primary power source. Diesel engines are known for their durability, fuel efficiency, and reliability. They are specifically designed for continuous or standby power generation and can provide a stable power supply for various applications.

Alternator: The generator set includes an alternator, which converts mechanical energy from the diesel engine into electrical energy. The alternator is responsible for generating the electric power output and maintaining a stable voltage and frequency.

Skid-Mounted Frame: The open type diesel generator is mounted on a sturdy skid base or frame. The skid base provides stability and allows for easy transportation and installation. It typically includes lifting points or forklift slots for convenient handling and positioning.

Cooling System: To maintain optimal operating temperature, the open type diesel generator incorporates a cooling system. It may include features such as a radiator, cooling fan, and coolant circulation system. The cooling system prevents overheating of the engine and ensures efficient and reliable performance.

Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ 730x495x630/ 730x495x655
Working Assorting Weight (kg):	66 83 110 115 120 125
Structure Type:	Open Type
Cylinder No. -bore X Stroke (mm):	1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 20Ah/ 12V 30Ah
Fuel Tank Capacity (L):	13.5
Rated Frequency:	50hz 60hz
Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
Rated Currency (A):	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	53 70 100 105 110 115
Noise Level (7m):	77 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	247 296 418 456 498 531
Compression Ratio:	20:01, 19:01
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	0.75 1.1 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280

Open type diesel generators are widely used in various applications where a reliable and portable power source is needed. They are commonly employed in construction sites, remote locations, agriculture, emergency backup power, and industrial settings.



性能 Specifications									
	1000000	1000000	1000000	1000000	1000000	1000000	1000000	1000000	1000000
处理器 (Processor)	Intel Core i7-10700K (8 cores, 16 threads, 5.0 GHz max)								
内存 (Memory)	32 GB DDR4-3200 (2x16 GB)								
硬盘 (Storage)	1 TB NVMe SSD								
显卡 (GPU)	NVIDIA GeForce RTX 3090 (24 GB VRAM)								
操作系统 (OS)	Windows 10 Pro 64-bit								
网络 (Network)	10 Gbps Ethernet, Wi-Fi 6E								
电源 (Power)	850 W 80+ Platinum								
机箱 (Case)	Mid Tower, ATX form factor								
接口 (Ports)	4x USB-A, 2x USB-C, 3x DisplayPort, 1x HDMI								
认证 (Certification)	Energy Star, EPEAT Silver								
保修 (Warranty)	3 years limited warranty								
其他 (Other)	Intel vPro, TPM 2.0								
备注 (Remarks)	All specifications are subject to change without notice.								