



9500T Ultra Silent Generator 50hz 60hz Ultra Quiet Diesel Generator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
- Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- Insulation Grade: F
- Pole Number: 2
- Excitation Mode: Self-excitation & Constant Voltage (AVR)
- Panel Type: General Panel
- Receptacle: Two Receptacles
- Operation Mode: Without

for more products please visit us on dieselenginepumps.com

Product Description

GET9500T Ultra Quiet Inverter Generator Ultra Silent Generator 50hz 60hz

Ultra-quiet portable generators offer several advantages over conventional generators, particularly in situations where noise reduction is important. Here are some key advantages of ultra-quiet portable generators:

Environmentally Friendly: Many ultra-quiet portable generators are engineered to be more fuel-efficient, reducing both fuel consumption and emissions. This not only benefits the environment but also extends the generator's runtime on a single tank of fuel. Additionally, some models offer the option to run on eco-mode, which adjusts the engine speed to match the power demand, further reducing fuel consumption and noise levels.

User-Friendly Features: Ultra-quiet portable generators often come equipped with user-friendly features for ease of operation. These can include electric start mechanisms, digital displays for monitoring power output and runtime, fuel gauges, and multiple outlets for connecting various devices simultaneously.

Reliable Power Source: Despite their quiet operation, ultra-quiet portable generators provide reliable power when you need it most. They are designed to deliver stable and consistent power output, ensuring the smooth operation of your essential electronics, appliances, or tools.

Safety Features: Ultra-quiet portable generators typically incorporate safety features such as overload protection, low-oil shutdown, and automatic voltage regulation. These features help protect the generator and connected devices from damage, ensuring safe and reliable operation.

Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	164 150 150 153 161
Noise Level (7m):	72 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	296 418 456 498 531
Compression Ratio:	20:01, 19:01
Starting System:	Electric Start
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 30Ah
Fuel Tank Capacity (L):	15
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	945*555*700
Working Assorting Weight (kg):	179 185 186 186 187
Structure Type:	Silent Type
Cylinder No. -bore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	1.1/ 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280
Continuous Running Time:	11h 8h 8h 7h 7h



参数表 Specifications

Model	GET-2500T	GET-4500T	GET-4800T	GET-5000T	GET-6300T
额定功率 (Rated Power) (kW)	2.5	4.5	4.8	5.0	6.3
额定电压 (Rated Voltage) (V)	220	220	220	220	220
额定频率 (Rated Frequency) (Hz)	50	50	50	50	50
额定转速 (Rated Speed) (r/min)	3000	3000	3000	3000	3000
额定排量 (Rated Displacement) (L)	2.96	4.18	4.56	4.98	5.31
额定油耗 (Rated Fuel Consumption) (g/kWh)	≤280	≤280	≤280	≤280	≤280
额定运行时间 (Rated Running Time) (h)	11	8	8	7	7
额定重量 (Rated Weight) (kg)	164	150	150	153	161
额定噪音 (Rated Noise) (dB)	72	72	72	72	72
额定尺寸 (Rated Dimensions) (mm)	945*555*700	945*555*700	945*555*700	945*555*700	945*555*700
额定启动系统 (Rated Starting System)	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start
额定燃油系统 (Rated Fuel System)	Pressure Splashed	Pressure Splashed	Pressure Splashed	Pressure Splashed	Pressure Splashed
额定冷却系统 (Rated Cooling System)	Air-cooled	Air-cooled	Air-cooled	Air-cooled	Air-cooled
额定绝缘等级 (Rated Insulation Grade)	F	F	F	F	F
额定连接方式 (Rated Connection Type)	Without	Without	Without	Without	Without
额定结构类型 (Rated Structure Type)	Silent Type	Silent Type	Silent Type	Silent Type	Silent Type
额定缸数 (Rated Cylinder No.)	1	1	1	1	1
额定缸径 (Rated Bore) (mm)	78	86	88	92	95
额定行程 (Rated Stroke) (mm)	62	72	75	75	75
额定压缩比 (Rated Compression Ratio)	20:01	20:01	20:01	20:01	20:01
额定启动电机容量 (Rated Starting Motor Capacity) (kW)	0.9	1.2	1.2	1.2	1.2
额定电池容量 (Rated Battery Capacity) (Ah)	30	30	30	30	30
额定燃油容量 (Rated Fuel Capacity) (L)	15	15	15	15	15
额定燃油消耗率 (Rated Fuel Consumption Rate) (g/kWh)	≤280	≤280	≤280	≤280	≤280
额定连续运行时间 (Rated Continuous Running Time) (h)	11	8	8	7	7



Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA