



15Hp 20Hp Single Cylinder Diesel Engine Recoil Or Electric Starter Diesel Engine

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Single Cylinder, Vertical, Four-stroke, Direct Injection, Air-cooled
- Borexstroke: 73x59mm, 78x62mm, 86x72mm
- Displacement: 247ml, 296ml, 418ml
- Compression Ratio: 20:01, 20:01, 19:01
- Rated Power(kw/rpm): 3.5/3000-3.8/3600 3.68/3000-4/3600 5.7/3000-6.3/3600
- Rated Power(hp/rpm): 4.8/3000-5.2/3600, 5.0/3000-5.4/3600, 7.8/3000-8.6/3600
- Rated Speed(rpm): 3000/3600
- Lowest Rotation Speed At Zero Load: ≤1300r/min
- Lubricating System: Pressure Splashed
- Starting System: Recoil Start/electric Starter
- Rotation Direction(face To The Output Axle): Anticlockwise
- Fuel Type: 0#(summer) 10#(winter) 25#(chillness)

for more products please visit us on diesenginepumps.com

GET 15 Hp 20 Hp Single Cylinder Diesel Engine Recoil Start Or Electric Starter

Light-duty generator sets: Since single-cylinder air-cooled diesel engines have low power loss and quick start-up characteristics, they are often used in small-scale generator sets, such as providing temporary power supply during camping, outdoor activities or emergency situations.

Ship auxiliary power: In the auxiliary power system of small ships or ships, single-cylinder air-cooled diesel engines are widely used. They are suitable for providing auxiliary power for ships, such as ship starting, navigation assistance, etc.

Communication equipment and mobile equipment: Since single-cylinder air-cooled diesel engines are small in size and have low power loss, they are often used to power communication equipment and mobile equipment. For example, in remote areas or places lacking power grid, single-cylinder air-cooled diesel engines can be used to provide power for communication base stations, mobile communication vehicles, mobile construction site equipment, etc.

Model	GET173F	GET186FA	GET178F
Bore x Stroke mm	296 x 418	-	-
Displacement mL	247	-	-
Compression Ratio	13.5/3000	3.68/3000	5.7/3000
Rated Power KW/rpm	4/3600	6.3/3600	3.8/3600
Rated Power HP/rpm	5.2/3600	5.4/3600	8.6/3600
Rated Speed/≤r/min	-	-	≤1300
Lubricating system	Pressure splashed	-	-
Starting system	Recoil Start/electric starter	-	-
Rotation direction(face to the output axle)	Anticlockwise	-	-
Fuel type	2.5L,3.5L,5.5L diesel	-	-
Fuel consumption/related rotation speed(g/kW.h///min)	288.3/3600,285.6/3600,281.5/3600	-	-
Lube oil type	CD grade or SAE 10W-30,15W-40,0.75,1.65L1.1	-	-
Lube oil capacity	12V,0.8kWV,kW	-	-
Starting motor capacity	V,A12V8.3ACharging generator capacity	-	-

[illegible]

